

**AMENDMENTS TO THE CLAIMS**

For the convenience of the Examiner, all claims have been presented whether or not an amendment has been made.

1. **(Withdrawn)** A transceiver module for use in an optical system, the transceiver comprising:

a housing configured for connection to a host;

a transceiver receptacle coupled to the housing, the transceiver receptacle having a first side defining a first interface portion and a second side defining a second interface portion;

a first adapter having a first connection portion configured to couple with the first interface portion;

a second adapter having a second connection portion configured to couple with the second interface portion; and

wherein the transceiver receptacle is configured to mate with a first front panel opening of a network device when the first and second adapters are not coupled with the transceiver receptacle, and wherein the transceiver receptacle is configured to mate with a second front panel opening of a network device when the first and second adapters are coupled with the transceiver receptacle, the first and second front panel openings of a network device being of different sizes.

2. **(Withdrawn)** The transceiver module of claim 1 wherein the first and second interface portions of the first and second sides are slots.

3. **(Withdrawn)** The transceiver module of claim 2 wherein the first and second connection portions of the first and second adaptors are arms extending from the adaptor, the arms of the first and second adapters being shaped to be received within the slots of the first and second sides of the transceiver receptacle.

4. **(Withdrawn)** The transceiver module of claim 1 wherein the first interface portion of the first side comprises a rear upper slot, a rear lower slot, a forward upper slot and



a forward lower slot, and wherein the second interface portion of the second side comprises a rear upper slot, a rear lower slot, a forward upper slot and a forward lower slot.

5. **(Withdrawn)** The transceiver module of claim 4 wherein the first connection portion of the first adaptor comprises a first arm and a second arm each extending from the first adaptor and wherein the first arm of the first adaptor is configured to be received within the forward upper slot of the first side and the second arm of the first adaptor is configured to be received within the rear upper slot of the first side, and wherein the second connection portion of the second adaptor comprises a first arm and a second arm each arm extending from the second adaptor and wherein the first arm of the second adaptor is configured to be received within the forward lower slot of the second side and the second arm of the second adaptor is configured to be received within the rear lower slot of the second side.

6. **(Withdrawn)** The transceiver module of claim 5 wherein the first adaptor and the second adaptor are identically configured.

7. **(Withdrawn)** The transceiver module of claim 1 wherein the first front panel opening of a network device is an MT-RJ shaped opening and wherein the second front panel opening of a network device is an LC shaped opening.

8. **(Withdrawn)** The transceiver module of claim 1 wherein the transceiver receptacle is between 8.1mm and 9.1mm in height and wherein the transceiver receptacle is the between 9.1mm and 10.1mm in width when the first and second adapters are not coupled with the transceiver receptacle and between 12.4mm and 13.3mm in width when the first and second adapters are coupled with the transceiver receptacle.

9. **(Withdrawn)** The transceiver module of claim 1 further including a first collar removably coupled over the transceiver receptacle when the first and second adapters are not coupled with the transceiver receptacle, and a second collar removably coupled over the transceiver receptacle when the first and second adapters are coupled with the transceiver receptacle, both the first and second collars having a plurality of springs coupled thereto.



10. (Currently Amended) A transceiver assembly comprising:

a transceiver module having a first end configured to be coupled with a host device and a second end configured to be coupled to the front panel opening of a network device, the second end having a first dimension and having an initial second dimension, wherein the first end of the transceiver module comprises a housing configured for connection to the host device and the second end of the transceiver module comprises a transceiver receptacle coupled to the housing;

a first adapter;

a second adapter;

first connection means for coupling the first adapter to the second end of the transceiver module;

second connection means for coupling the second adapter to the second end of the transceiver module; and

wherein connecting the first and second adapter to the second end of the transceiver module changes the initial second dimension to a converted second dimension that is different from the initial second dimension; and

wherein the transceiver receptacle has a first side defining a first interface portion and a second side defining a second interface portion, wherein the first adapter has a first connection portion configured to couple with the first interface portion, wherein the second adapter has a second connection portion configured to couple with the second interface portion, and wherein the transceiver receptacle is configured to mate with a first front panel opening of a network device when the first and second adapters are not coupled with the transceiver receptacle, and wherein the transceiver receptacle is configured to mate with a second front panel opening of a network device when the first and second adapters are coupled with the transceiver receptacle, the first and second front panel openings of a network device being of different sizes.

11. (Canceled)

12. (Canceled)

13. (Canceled)



14. **(Original)** The transceiver module of claim 10 wherein the first and second adapters are coupled to the second end of the transceiver module using an adhesive.

15. **(Original)** The transceiver module of claim 10 wherein the first adaptor and the second adaptor are identically configured.

16. **(Canceled)**

17. **(Canceled)**



18. **(Withdrawn)** A method for converting a transceiver initially configured to interface with a first-sized front panel opening of a network device to a transceiver configured to interface with a second-sized front panel opening of a network device comprising:

providing the transceiver with a receptacle configured to be coupled with the first-sized front panel opening of a network device and with an end configured to be coupled with a host device, the receptacle having a first and a second side, wherein the first and second sides each define interface portions;

coupling a first adapter to the first side of the receptacle, the first adapter having a connection portion configured to couple with the interface portion defined by the first side of the receptacle;

coupling a second adapter to the second side of the receptacle, the second adapter having a connection portion configured to couple with the interface portion defined by the second side of the receptacle; and

wherein the transceiver receptacle mates with the second sized-optical connector after the first and second adapters are coupled to the transceiver receptacle.

19. **(Withdrawn)** The method of claim 18 further including coupling the transceiver receptacle to a front panel opening of a network device having an LC shape after the first and second adapters are coupled to the transceiver receptacle.

20. **(Canceled)**

21. **(Canceled)**

22. **(Canceled)**

23. **(Currently Amended)** The transceiver module of claim 22 10 wherein the first and second interface portions of the first and second sides are slots.

24. **(Original)** The transceiver module of claim 23 wherein the first and second connection portions of the first and second adaptors are arms extending from the adaptor, the



arms of the first and second adapters being shaped to be received within the slots of the first and second sides of the transceiver receptacle.

25. **(Currently Amended)** The transceiver module of claim 22 10 wherein the first interface portion of the first side comprises a rear upper slot, a rear lower slot, a forward upper slot and a forward lower slot, and wherein the second interface portion of the second side comprises a rear upper slot, a rear lower slot, a forward upper slot and a forward lower slot.

26. **(Previously Presented)** The transceiver module of claim 25 wherein the first connection portion of the first adaptor comprises a first arm and a second arm each extending from the first adaptor and wherein the first arm of the first adaptor is configured to be received within the forward upper slot of the first side and the second arm of the first adaptor is configured to be received within the rear upper slot of the first side, and wherein the second connection portion of the second adaptor comprises a first arm and a second arm each arm extending from the second adaptor and wherein the first arm of the second adaptor is configured to be received within the forward lower slot of the second side and the second arm of the second adaptor is configured to be received within the rear lower slot of the second side.

27. **(Canceled)**

28. **(Currently Amended)** The transceiver module of claim 22 10 wherein the first front panel opening of a network device is an MT-RJ shaped opening and wherein the second front panel opening of a network device is an LC shaped opening.

29. **(Currently Amended)** The transceiver module of claim 22 10 wherein the transceiver receptacle is between 8.1mm and 9.1mm in height and wherein the transceiver receptacle is the between 9.1mm and 10.1mm in width when the first and second adapters are not coupled with the transceiver receptacle and between 12.4mm and 13.3mm in width when the first and second adapters are coupled with the transceiver receptacle.



30. **(Currently Amended)** The transceiver module of claim ~~22~~ 10 further including a first collar removably coupled over the transceiver receptacle when the first and second adapters are not coupled with the transceiver receptacle, and a second collar removably coupled over the transceiver receptacle when the first and second adapters are coupled with the transceiver receptacle, both the first and second collars having a plurality of springs coupled thereto.